



Pillar Jib Crane Underbraced 270° Movable PFI MOB

Product information

The headroom is the main asset of the PFI MOB. Appropriate for an indoor or outdoor use, its I beam profile allows to consider installation of a hoist with electric or manual steering. This jib crane is mounted on a movable concrete block provided. Displacement can be done by traveling crane (transport ring) or by forklift.

A full range of accessories is available.

Options

- Hoist power supply cable
- Lockable main switch
- Rotation slowing device
- Rotation stops to weld onto the assembly, or adjustable
- Single- or multipositions rotation lock
- Outdoor use
- Electric or manual hoist
- Hot dip galvanizing (contact us)

| Part code | WLL ton | Length m | Cap. kg |
|-----------------|------------|-------------|------------|
| 6025PFIMOB125 | 0.15 | 2 | 150 |
| PFIMOB0015-2500 | 0.15 | 2.5 | 150 |
| PFIMOB0015-3000 | 0.15 | 3 | 150 |
| PFIMOB0015-3500 | 0.15 | 3.5 | 150 |
| PFIMOB0015-4000 | 0.15 | 4 | 150 |
| PFIMOB0015-4500 | 0.15 | 4.5 | 150 |
| PFIMOB0015-5000 | 0.15 | 5 | 150 |
| PFIMOB0015-5500 | 0.15 | 5.5 | 150 |
| PFIMOB0015-6000 | 0.15 | 6 | 150 |
| 6025PFIMOB250 | 0.25 | 2 | 250 |
| PFIMOB0025-2500 | 0.25 | 2.5 | 250 |
| PFIMOB0025-3000 | 0.25 | 3 | 250 |
| PFIMOB0025-3500 | 0.25 | 3.5 | 250 |
| PFIMOB0025-4000 | 0.25 | 4 | 250 |
| PFIMOB0025-4500 | 0.25 | 4.5 | 250 |
| PFIMOB0025-5000 | 0.25 | 5 | 250 |
| 6025PFIMOB500 | 0.5 | 2 | 500 |
| PFIMOB0050-2500 | 0.5 | 2.5 | 500 |
| PFIMOB0050-3000 | 0.5 | 3 | 500 |