

Swivel Jaw / Hook Crosby S1

Product information



Design: Swivel with jaw and hook equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250t available on demand.

... [Read more](#)

Marking: CE-marked


Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

Swivel Jaw / Hook Crosby S1

Blueprint



Technical data

| Part code | Rope Ø range mm | WLL ton | Swivel No | A mm | F mm | G mm | H mm | J mm | K mm | L mm | M mm | N mm | O mm | P mm | V mm | Weight kg |
|-------------|-----------------|---------|-----------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|
| 11.46297011 | 13 | 3 | 3-S-1 | 291 | 123 | 70 | 19.1 | 22.4 | 41.1 | 38.9 | 35.8 | 33.3 | 25.4 | 36.6 | 28.4 | 4.45 |
| 11.46297217 | 16 | 5 | 5-S-1 | 339 | 160 | 76 | 22.4 | 25.4 | 57 | 49.3 | 42.9 | 41.1 | 28.4 | 46 | 36.6 | 7.04 |
| 11.46297413 | 19 | 8.5 | 8-S-1 | 418 | 192 | 102 | 25.4 | 39.5 | 71.5 | 62.5 | 56.5 | 54 | 35.1 | 57 | 41.1 | 13.3 |
| 11.46297618 | 22 | 10 | 10-S-1 | 502 | 212 | 114 | 38.1 | 44.5 | 86 | 66 | 61 | 89 | 44.5 | 66 | 49.3 | 21.2 |
| 11.46297814 | 26 | 15 | 15-S-1 | 565 | 263 | 127 | 38.1 | 44.5 | 86 | 71.5 | 81 | 89 | 44.5 | 76 | 60.5 | 33.5 |
| 11.46298118 | | 25 | 25-S-1 | 680 | 346 | 152 | 51 | 51 | 117 | 87.5 | 92 | 93.5 | 60.5 | 93 | 76 | 64 |
| 11.46298216 | | 35 | 35-S-1 | 760 | 357 | 165 | 51 | 51 | 117 | 98.5 | 95.5 | 93.5 | 60.5 | 116 | 81 | 100 |
| 11.46298314 | | 45 | 45-S-1 | 891 | 392 | 178 | 57 | 63.5 | 127 | 121 | 108 | 102 | 76 | 129 | 82.5 | 114 |