MENNENS | Lifting Solutions Group
Axel Johnson International

Swivel Jaw / Eye Crosby S3

Product information



Produktinformasjon

Produktegenskaper

- Egnet for hyppig rotasjon under last. - Alle svivler er individuelt prøvebelastet til 2 ganger arbeidslastgrensen (WLL). - Utstyrt med smørenippel. - Alle gafler leveres komplette med bolter, muttere og splinter. - Andre typer og kapasiteter opp til 1250 t tilgjengelig på forespørsel.

Andre opplysninger

- **Design:** Svivel med gafler utstyrt med konisk rulletrykklager.
- **Prøvebelastning:** 2x WLL

... *Read more*

Marking: CE-mark
Note: Always check before use if your steel wire rope is suitable for use with a swivel.
Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Swivel Jaw / Eye Crosby S3

Blueprint



Technical data

Part code	Rope Ø range mm	WLL ton	Swivel No	C mm	G mm	H mm	J mm	K mm	N mm	O mm	Q mm	R mm	S mm	T mm	Weight kg
422500300090	13	3	3-S-3	237	70	19.1	22.4	41.1	33.3	25.4	19.1	26.2	28.4	31.8	4.14
422500500090	16	5	5-S-3	256	76	22.4	25.4	57	41.1	28.4	25.4	32.5	31.8	31.8	6.12
422500850090	19	8.5	8-S-3	311	102	25.4	39.5	71.5	54	35.1	31.8	35.8	41.1	38.1	11.3
422501000090	22	10	10-S-3	409	114	38.1	44.5	86.1	89	44.5	42.9	42.9	70	47.8	19.7
422501500090	26	15	15-S-3	425	127	38.1	44.5	86	89	44.5	49.3	51.5	70	54	27.7
422502500090		25	25-S-3	546	152	51	51	117	93.5	60.5	57	58.5	98.5	60.5	61
422503500090		35	35-S-3	546	165	51	51	117	93.5	60.5	57	58.5	98.5	60.5	68
422504500090		45	45-S-3	657	178	57	63.5	127	102	76	63.5	64.5	102	76	102

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved