Lifting Solutions Group
Axel Johnson International

# Swivel Regular Crosby G-402

## Product information



**Design:** Chain swivels with out bearing. According to Federal Specification RR-C-271F.

... *Read more*

**Material:** Hot dip Galvanized - Quenched & Tempered
**Marking:** WLL
**Finish:** Galvanized
**Note:** The swivels are positioning devices and are not intended to rotate under load. For load swivels, see ball bearing swivels.

**Safety factor:** 5:1


**Mennens Belgium**
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

# Swivel Regular Crosby G-402

## Blueprint




## Technical data

| Part code | Diameter mm | WLL ton | A mm | B mm | C mm | D mm | J mm | M mm | R mm | S mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 422500060120 | 8 | 0.57 | 41.4 | 20.6 | 25.4 | 31.8 | 20.6 | 9.65 | 90.4 | 52.3 | 0.18 |
| 422500100120 | 10 | 1.02 | 51 | 23.9 | 31.8 | 38.1 | 25.4 | 12.7 | 109 | 63.5 | 0.32 |
| 422500160120 | 13 | 1.63 | 63.5 | 33.3 | 38.1 | 51 | 33.3 | 16 | 138 | 81 | 0.6 |
| 422500240120 | 16 | 2.36 | 76 | 39.5 | 44.5 | 60.5 | 38.1 | 19.1 | 167 | 98.5 | 1.13 |
| 422500330120 | 19 | 3.27 | 89 | 44.5 | 51 | 67 | 47.8 | 22.4 | 183 | 109 | 1.82 |
| 422500450120 | 22 | 4.54 | 102 | 52 | 57 | 77.5 | 54 | 25.4 | 213 | 127 | 2.83 |
| 422500570120 | 25 | 5.67 | 114 | 58.5 | 63.5 | 89 | 60.5 | 28.7 | 245 | 146 | 4.06 |
| 422500820120 | 32 | 8.16 | 143 | 68.5 | 79.5 | 93.5 | 76 | 38.1 | 291 | 172 | 7.42 |
| 422502050120 | 38 | 20.5 | 180 | 98.5 | 104 | 98.5 | 95.2 | 57 | 424 | 252 | 20.8 |

**Mennens Belgium**
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved