

Short Link Lifting Chain POWERTEX PSL

Product information



POWERTEX

The POWERTEX PSL Short Link Lifting Chain is a calibrated Grade 10 lifting chain for demanding lifting applications, including building Grade 10 chain slings. It combines reliable mechanical performance with consistent manufacturing and full traceability for professional industrial lifting.

Best used for

- Grade 10 chain sling assembly
- Industrial lifting applications requiring calibrated lifting chain

Product benefits

- Proof load tested to $2.5 \times \text{WLL}$ before delivery
- Every production batch tested for minimum breaking force
- Calibrated chain supports accurate sling assembly
- Automatic welding delivers consistent chain quality
- Minimum 20% elongation provides controlled ductility before failure
- Water-based wet spray blue finish for durable corrosion protection
- Manufactured in Europe and compliant with Machinery Directive 2006/42/EC
- CE, UKCA and traceability marked with 2.2 Certificate and Declaration of Conformity included

[... Read more](#)

Material: Quenched and Tempered Alloy Steel of Grade 10 quality

Marking: According to standard, CE-marked, UKCA-marked, Factory symbol, Grade (10), Traceability batch marking

Temperature range: -40°C up to $+200^{\circ}\text{C}$ without reduction in WLL

Finish: Water based wet spray blue painted


Standard: EN 818-2 (+ 25% WLL), AS 2321, ASTM A973/A973M

Safety factor: 4:1

Grade: 10

Short Link Lifting Chain POWERTEX PSL

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length mm	Model	d mm	p mm	W1 min mm	W2 max mm	Weight kg/m
203500600000010	6	1.4	56.5	18	PSL-6-10	6	18	7,8	22,2	0.8
203500700000010	7	1.9	77	21	PSL-7-10	7	21	9,1	25,9	1.2
203500800000010	8	2.5	101	24	PSL-8-10	8	24	10,4	29,6	1.5
203501000000010	10	4	157	30	PSL-10-10	10	30	13,0	37,0	2.3
203501300000010	13	6.7	265	39	PSL-13-10	13	39	16,9	48,1	3.9
203501600000010	16	10	402	48	PSL-16-10	16	48	20,8	59,2	5.8
203501900000010	19	14	567	57	PSL-19-10	19	57	24,7	70,3	8.4
203502000000010	20	16	628	60	PSL-20-10	20	60	26,0	74,0	8.9
203502200000010	22	19	760	66	PSL-22-10	22	66	28,6	81,4	11.4
203502600000010	26	26.5	1,060	78	PSL-26-10	26	78	33,8	96,2	16
203503200000010	32	40	1,610	96	PSL-32-10	32	96	41,6	118	24.1