



## Gantry Crane, Porta Gantry 500-5000kg

### Product information

**General:** Lightweight Gantry Crane for lifting of goods and persons.

**Goods WLL:** From 500kg up to 5000kg (depending on model)

**Personnel WLL:** Maximum combined personnel lifting capacity up to 2000kg (depending on model)

**3-5 Person fall arrest:** EN795:1997 certified – as part of an EN363 compliant system (500 & 1000 - 3 persons, 2000, 3000 & 5000 - 5 persons)

**ATEX:** All models suitable for use in ATEX Zone 2 explosive atmospheres

**Lightweight & portable:** With easy on-site assembly within manual handling guidelines:

- 4 portable parts assembled on just 4 bolts
- Simple 'scissoring' assembly in just 2-3 minutes

**Ergonomic**

- 360° swivel-locking castors as standard
- Simple, manual height & span adjustment
- Ultra-safe captive trolley
- Ergonomic design of profiles and handles

**Stable:** Bolted structure, lateral beam and leg bracing features

**Configurations:** Variety of standard configurations available, plus customisation for specific requirements and interchangeable components (subject to WLL rating)

WLL Rating	Standard Beam Length
kg	mm
-	9,000
-	Weight of Beams
-	kg
500	19
1,000	84
2,000	x
3,000	x
5,000	x