

HSC S Short Stroke Hydraulic Cylinder



Product information

Holmatro Short stroke cylinders (HSC) - Spring return

Unique specifications:

- Compact version, efficient in case of limited insertion space
- Stroke of 50mm on all models

Standard supplied with:

- Dirt scraper ring
 - Protects against pollution
 - Increases the life span
- Superior seal for an excellent static and dynamic sealing
- Splined plunger, no saddle needed
- High flow female coupler A118

Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Steel

| Part code | Code | WLL ton | Stroke mm | Closed height mm | required oil cc | Capacity kN/t | Weight kg |
|----------------|-------------|---------|-----------|------------------|-----------------|----------------|-----------|
| 16.40100112300 | HSC 10 S 5 | 10 | 50 | 100 | 69.3 | 99.8 / 10.2 | 2.9 |
| 16.40100112301 | HSC 20 S 5 | 20 | 50 | 103 | 141.4 | 203.6 / 20.8 | 5.5 |
| 16.40100112302 | HSC 30 S 5 | 30 | 50 | 106 | 221 | 318.1 / 32.4 | 6.1 |
| 16.40100112303 | HSC 50 S 5 | 50 | 50 | 117 | 354 | 510.4 / 52 | 9.7 |
| 16.40100112304 | HSC 100 S 5 | 100 | 50 | 141 | 716 | 1030.6 / 105.1 | 22.2 |

Blueprint

