Vari Pump Twin - 400V - 1 Stage T

Product information



Vari pump Twin, single-stage 400 V – 50 Hz – 3ph. Standard supplied with 3/8” NPT female thread. Excluding coupler, hoses and pressure gauge.

To control your hydraulic system, Holmatro offers a various range of pump units:

- 230V, 400V or petrol driven
- 1 or 2 stage

Unique specifications:

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for feature use; ad a Sada switch (M304) to your pump set-up

You want to make sure you choose the right vari-pump for your application? Download the Holmatro Vari pump configurator.

Additional information:

To have a safe and controlled system, assemble your vari-pump with advised components:

- Option A: 1 cylinder application : assemble a pressure gauge directly on the pump unit
- Option B: multiple cylinder application: add a flow panel & assembly set to your pump set-up
- TIP: download the vari-pump configurator for more info

Why add a pressure gauge or flowpanel?

... *Read more*

Features: - 2 separate outlets.
Note: Excluding single-acting or double-acting control valve.

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Vari Pump Twin - 400V - 1 Stage T

Technical data

Part code	Code	Max. working pressure bar/Mpa	oil capacity cc	Engine	Weight kg
5201100152072	09 T 12 E	720 / 72	12,000	400 VAC-2.2 kW-50 Hz-3 PH	52
5201100152073	09 T 25 E	720 / 72	25,000	400 VAC-1.5 kW-50 Hz-3 PH	71

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved