



Hydraulic Hoses - H1 SO

Product information

Holmatro hose for high pressure hydraulics. No coupler(s) included

Features & benefits:

- Suitable for high pressure hydraulics / max 700bar working pressure
- Anti-kink spring on both sides
- All hoses are individually tested during the production proces.
- Safety factor 4:1
- 6 Year max. lifespan.

Standard supplied with:

- Hose connection A = 3/8" NPT male
- Hose connection B = 3/8" NPT male
- Already filled with oil.

Also available:

- Hydraulic cylinders
- Hydraulic pump units 700bar to control the cylinder(s)
- System components to complete your hydraulic system

Available on request:

- Different lengths.
- Other colour.

| Code | Size | max. working pressure bar / Mpa | connection A | connection B |
|---------|------|------------------------------------|---------------|---------------|
| H 1 SO | 1 m | 720 / 72 | 3/8" NPT male | 3/8" NPT male |
| H 10 SO | 10 m | 720 / 72 | 3/8" NPT male | 3/8" NPT male |
| H 2 SO | 2 m | 720 / 72 | 3/8" NPT male | 3/8" NPT male |
| H 3 SO | 3 m | 720 / 72 | 3/8" NPT male | 3/8" NPT male |
| H 5 SO | 5 m | 720 / 72 | 3/8" NPT male | 3/8" NPT male |