

Chain Sling CSX-175 Grade 10

Product information



Design: Chain sling with master link on one end and clevis load hook on the other end.

∅ 26 mm chain is fitted with an eye hook. Other combinations possible on demand.

Dimensions: ∅ 6–26 mm (other dimensions on demand).

[... Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Chain Sling CSX-175 Grade 10

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m |
|------------------|----------------------|------------|----------|
| 11.91CSX17506XXX | 6 | 1.4 | - |
| 11.91CSX17506005 | 6 | 1.4 | 0.5 |
| 11.91CSX17506010 | 6 | 1.4 | 1 |
| 11.91CSX17506015 | 6 | 1.4 | 1.5 |
| 11.91CSX17506020 | 6 | 1.4 | 2 |
| 11.91CSX17506030 | 6 | 1.4 | 3 |
| 11.91CSX17506040 | 6 | 1.4 | 4 |
| 11.91CSX17506050 | 6 | 1.4 | 5 |
| 11.91CSX17506060 | 6 | 1.4 | 6 |
| 11.91CSX17507XXX | 7 | 1.9 | - |
| 11.91CSX17507005 | 7 | 1.9 | 0.5 |
| 11.91CSX17507010 | 7 | 1.9 | 1 |
| 11.91CSX17507015 | 7 | 1.9 | 1.5 |
| 11.91CSX17507020 | 7 | 1.9 | 2 |
| 11.91CSX17507030 | 7 | 1.9 | 3 |
| 11.91CSX17507040 | 7 | 1.9 | 4 |
| 11.91CSX17507050 | 7 | 1.9 | 5 |
| 11.91CSX17507060 | 7 | 1.9 | 6 |
| 11.91CSX17508XXX | 8 | 2.5 | - |
| 11.91CSX17508005 | 8 | 2.5 | - |
| 11.91CSX17508010 | 8 | 2.5 | - |
| 11.91CSX17508015 | 8 | 2.5 | - |
| 11.91CSX17508020 | 8 | 2.5 | - |
| 11.91CSX17508030 | 8 | 2.5 | - |
| 11.91CSX17508040 | 8 | 2.5 | - |
| 11.91CSX17508050 | 8 | 2.5 | - |
| 11.91CSX17508060 | 8 | 2.5 | - |
| 11.91CSX17510XXX | 10 | 4 | - |
| 11.91CSX17510005 | 10 | 4 | - |
| 11.91CSX17510010 | 10 | 4 | - |
| 11.91CSX17510015 | 10 | 4 | - |

Chain Sling CSX-175 Grade 10

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m |
|------------------|----------------------|------------|----------|
| 11.91CSX17510020 | 10 | 4 | - |
| 11.91CSX17510030 | 10 | 4 | - |
| 11.91CSX17510040 | 10 | 4 | - |
| 11.91CSX17510050 | 10 | 4 | - |
| 11.91CSX17510060 | 10 | 4 | - |
| 11.91CSX17513XXX | 13 | 6.7 | - |
| 11.91CSX17513005 | 13 | 6.7 | - |
| 11.91CSX17513010 | 13 | 6.7 | - |
| 11.91CSX17513015 | 13 | 6.7 | - |
| 11.91CSX17513020 | 13 | 6.7 | - |
| 11.91CSX17513030 | 13 | 6.7 | - |
| 11.91CSX17513040 | 13 | 6.7 | - |
| 11.91CSX17513050 | 13 | 6.7 | - |
| 11.91CSX17513060 | 13 | 6.7 | - |
| 11.91CSX17516XXX | 16 | 10 | - |
| 11.91CSX17516005 | 16 | 10 | - |
| 11.91CSX17516010 | 16 | 10 | - |
| 11.91CSX17516015 | 16 | 10 | - |
| 11.91CSX17516020 | 16 | 10 | - |
| 11.91CSX17516030 | 16 | 10 | - |
| 11.91CSX17516040 | 16 | 10 | - |
| 11.91CSX17516050 | 16 | 10 | - |
| 11.91CSX17516060 | 16 | 10 | - |
| 11.91CSX17519XXX | 19 | 14 | - |
| 11.91CSX17519005 | 19 | 14 | - |
| 11.91CSX17519010 | 19 | 14 | - |
| 11.91CSX17519015 | 19 | 14 | - |
| 11.91CSX17519020 | 19 | 14 | - |
| 11.91CSX17519030 | 19 | 14 | - |
| 11.91CSX17519040 | 19 | 14 | - |
| 11.91CSX17519050 | 19 | 14 | - |

Chain Sling CSX-175 Grade 10

Technical data

| Part code | Chain diameter mm | WLL ton | EWL m |
|------------------|----------------------|------------|----------|
| 11.91CSX17519060 | 19 | 14 | - |
| 11.91CSX17522XXX | 22 | 19 | - |
| 11.91CSX17522005 | 22 | 19 | - |
| 11.91CSX17522010 | 22 | 19 | - |
| 11.91CSX17522015 | 22 | 19 | - |
| 11.91CSX17522020 | 22 | 19 | - |
| 11.91CSX17522030 | 22 | 19 | - |
| 11.91CSX17522040 | 22 | 19 | - |
| 11.91CSX17522060 | 22 | 19 | - |
| 11.91CSX17526XXX | 26 | 26.5 | - |
| 11.91CSX17526005 | 26 | 26.5 | - |
| 11.91CSX17526010 | 26 | 26.5 | - |
| 11.91CSX17526015 | 26 | 26.5 | - |
| 11.91CSX17526020 | 26 | 26.5 | - |
| 11.91CSX17526030 | 26 | 26.5 | - |
| 11.91CSX17526040 | 26 | 26.5 | - |
| 11.91CSX17526050 | 26 | 26.5 | - |
| 11.91CSX17526060 | 26 | 26.5 | - |