


## Chain Sling CSX-176 Grade 10

---

### Product information



**Design:** Chain sling with master link on one end and clevis safety hook on the other end.

∅ 19 and 22 mm chain are fitted with an eye safety hook. Other combinations possible on demand.

**Dimensions:** ∅ 6–22 mm (other dimensions on demand).

[... Read more](#)

---

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 200°C (up to 380° possible on demand)

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling CSX-176 Grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17606XXX	6	1.4	-
11.91CSX17606005	6	1.4	0.5
11.91CSX17606010	6	1.4	1
11.91CSX17606015	6	1.4	1.5
11.91CSX17606020	6	1.4	2
11.91CSX17606030	6	1.4	3
11.91CSX17606040	6	1.4	4
11.91CSX17606050	6	1.4	5
11.91CSX17606060	6	1.4	6
11.91CSX17607XXX	7	1.9	-
11.91CSX17607005	7	1.9	0.5
11.91CSX17607010	7	1.9	1
11.91CSX17607015	7	1.9	1.5
11.91CSX17607020	7	1.9	2
11.91CSX17607030	7	1.9	3
11.91CSX17607040	7	1.9	4
11.91CSX17607050	7	1.9	5
11.91CSX17607060	7	1.9	6
11.91CSX17608XXX	8	2.5	-
11.91CSX17608005	8	2.5	0.5
11.91CSX17608010	8	2.5	1
11.91CSX17608015	8	2.5	1.5
11.91CSX17608020	8	2.5	2
11.91CSX17608030	8	2.5	3
11.91CSX17608040	8	2.5	4
11.91CSX17608050	8	2.5	5
11.91CSX17608060	8	2.5	6
11.91CSX17610XXX	10	4	-
11.91CSX17610005	10	4	0.5
11.91CSX17610010	10	4	1
11.91CSX17610015	10	4	1.5

## Chain Sling CSX-176 Grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17610020	10	4	2
11.91CSX17610030	10	4	3
11.91CSX17610040	10	4	4
11.91CSX17610050	10	4	5
11.91CSX17610060	10	4	6
11.91CSX17613XXX	13	6.7	-
11.91CSX17613005	13	6.7	0.5
11.91CSX17613010	13	6.7	1
11.91CSX17613015	13	6.7	1.5
11.91CSX17613020	13	6.7	2
11.91CSX17613030	13	6.7	3
11.91CSX17613040	13	6.7	4
11.91CSX17613050	13	6.7	5
11.91CSX17613060	13	6.7	6
11.91CSX17616XXX	16	10	-
11.91CSX17616005	16	10	0.5
11.91CSX17616010	16	10	1
11.91CSX17616015	16	10	1.5
11.91CSX17616020	16	10	2
11.91CSX17616030	16	10	3
11.91CSX17616040	16	10	4
11.91CSX17616050	16	10	5
11.91CSX17616060	16	10	6
11.91CSX17619XXX	19	14	-
11.91CSX17619005	19	14	0.5
11.91CSX17619010	19	14	1
11.91CSX17619015	19	14	1.5
11.91CSX17619020	19	14	2
11.91CSX17619030	19	14	3
11.91CSX17619040	19	14	4
11.91CSX17619050	19	14	5

## Chain Sling CSX-176 Grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m
11.91CSX17619060	19	14	6
11.91CSX17622XXX	22	19	-
11.91CSX17622005	22	19	0.5
11.91CSX17622010	22	19	1
11.91CSX17622015	22	19	1.5
11.91CSX17622020	22	19	2
11.91CSX17622030	22	19	3
11.91CSX17622040	22	19	4
11.91CSX17622050	22	19	5
11.91CSX17622060	22	19	6