MENNENS | Lifting Solutions Group
Axel Johnson International

Chain Sling CSX-375 Grade 10

Product information



Design: Chain sling with master link on one end and clevis load hook on the other end of each leg.
ø 26 mm chain is fitted with eye hooks. Other combinations possible on demand.

Dimensions: Ø 6–26 mm (other dimensions on demand).

... Read more

Material: Alloy steel.
Marking: According to standard, CE-mark
Temperature range: -40°C up to 200°C (up to 380° possible on demand)
Standard: EN 818-4
Warning: Not to be heat-treated.

Safety factor: 4:1
Grade: 10

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Chain Sling CSX-375 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
2412	6	3	-
2412	6	3	0.5
2412	6	3	1
2412	6	3	1.5
2412	6	3	2
2412	6	3	3
2412	6	3	4
2412	6	3	5
2412	6	3	6
2412	7	4	-
2412	7	4	0.5
2412	7	4	1
2412	7	4	1.5
2412	7	4	2
2412	7	4	3
2412	7	4	4
2412	7	4	5
2412	7	4	6
2412	8	5.3	-
2412	8	5.3	0.5
2412	8	5.3	1
2412	8	5.3	1.5
2412	8	5.3	2
2412	8	5.3	3
2412	8	5.3	4
2412	8	5.3	5
2412	8	5.3	6
2412	10	8	-
2412	10	8	0.5
2412	10	8	1
2412	10	8	1.5

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23
© November 2026 - All Rights Reserved

Chain Sling CSX-375 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
2412	10	8	2
2412	10	8	3
2412	10	8	4
2412	10	8	5
2412	10	8	6
2412	13	14	-
2412	13	14	0.5
2412	13	14	1
2412	13	14	1.5
2412	13	14	2
2412	13	14	3
2412	13	14	4
2412	13	14	5
2412	13	14	6
2412	16	21.2	-
2412	16	21.2	0.5
2412	16	21.2	1
2412	16	21.2	1.5
2412	16	21.2	2
2412	16	21.2	3
2412	16	21.2	4
2412	16	21.2	5
2412	16	21.2	6
2412	19	30	-
2412	19	30	0.5
2412	19	30	1
2412	19	30	1.5
2412	19	30	2
2412	19	30	3
2412	19	30	4
2412	19	30	5

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Chain Sling CSX-375 Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m
2412	19	30	6
2412	22	40	-
2412	22	40	0.5
2412	22	40	1
2412	22	40	1.5
2412	22	40	2
2412	22	40	3
2412	22	40	4
2412	22	40	5
2412	22	40	6
2412	26	56	0.5
2412	26	56	1
2412	26	56	1.5
2412	26	56	2
2412	26	56	3
2412	26	56	4
2412	26	56	5
2412	26	56	6
2412	26	56	-

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved