



Eye Sling Hook Pewag HSWP

Product information

This eye sling hook is ideally suited for the pewag winner pro Connex system. It is universally usable and comes with a forged and galvanised safety catch that locks into the tip of the hook, thereby providing excellent protection against lateral shifts. The safety catch with a latch, the safety pin and the stainless spring are available as a spare parts set for each hook and easy and quick to replace by a competent person.

Material: Alloy steel.

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

Temperature range: -60°C up to +300°C.

Finish: Light blue powdercoated.

Standard: EN 1677-2

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 12

| Part code | Code | WLL ton | LC kN | EWL | a mm | b mm | d1 mm | d2 mm | e mm | g1 mm | h mm | Weight kg |
|------------|----------|------------|----------|-----|---------|---------|----------|----------|---------|----------|---------|--------------|
| 11.1288001 | HSWP 7/8 | 3 | 60 | 106 | 19 | 88 | 25 | 11 | 106 | 26 | 27 | 0.65 |
| 11.1288003 | HSWP 10 | 5 | 100 | 131 | 26 | 108 | 34 | 16 | 131 | 31 | 33 | 1.29 |
| 11.1288005 | HSWP 13 | 8 | 160 | 164 | 33 | 132 | 43 | 19 | 164 | 39 | 43 | 2.43 |

Blueprint

