

Winner 200 Chain Pewag

Product information



Round steel chains for use in lifting or lashing chains.

Material: High duty chain.

Marking: According to standard, Each chain link is marked with 10 for grade 10 and the chain is marked pewag 10 (PWA 100).

Temperature range: -40°C up to +200°C.

Finish: Blasted, clear painted.

Standard: EN 818-2

Safety factor: 4:1

Grade: 10

| Part code | Chain diameter mm | WLL ton | Min. breaking force kN | dn mm | t mm | b1 mm | b2 mm | Weight kg/m |
|------------|----------------------|------------|---------------------------|----------|---------|----------|----------|----------------|
| 11.653959 | 6 | 1.4 | 56.5 | 6 | 18 | 8.7 | 21.6 | 0.96 |
| 11.653973 | 7 | 1.9 | 77 | 7 | 21 | 9.5 | 25.2 | 1.2 |
| 11.653975 | 8 | 2.5 | 101 | 8 | 24 | 10.9 | 28.8 | 1.57 |
| 11.653976 | 10 | 4 | 157 | 10 | 30 | 13.5 | 37 | 2.46 |
| 11.653986 | 13 | 6.7 | 265 | 13 | 39 | 17.5 | 46.8 | 4.18 |
| 11.653988 | 16 | 10 | 402 | 16 | 48 | 21.5 | 57.6 | 6.28 |
| 11.653989 | 19 | 14 | 567 | 19 | 57 | 26.6 | 69.4 | 8.92 |
| 11.654043 | 22 | 19 | 760 | 22 | 66 | 29.5 | 79.2 | 11.88 |
| 11.6572801 | 26 | 26.5 | 1,006 | 26 | 78 | 35 | 94 | 16.18 |
| 11.6514245 | 32 | 40 | 1,610 | 32 | 96 | 43.2 | 115 | 24.1 |

Blueprint

