



## Master Link Pewag AW

### Product information

AW Master links are designed for the assembly of chain slings. For pewag connex and welded system.

Master link for 1-leg chain AI.

Master link for 2-leg chain AII.

Master link for 3- and 4-leg chain AIII/IV - only with transition link BW as on VW.

Can also be used as end link A I

**Material:** High duty

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	LC kN	EWL	For chain, 1-leg mm	For chain, 2-leg mm	d mm	s mm	t mm	w mm	Weight kg
11.0246775	AW 13	2.3	46	110	6+7	6	13	10	110	60	0.34
11.0246776	AW 16	3.5	70	110	8	7	16	14	110	60	0.53
11.0246777	AW 18	5	100	135	10	8	19	14	135	75	0.92
11.0246778	AW 22	7.6	152	160	13	10	23	17	160	90	1.6
11.0246779	AW 26	10	200	180	16	13	27	20	180	100	2.46
11.0246780	AW 32	14	280	200	19	16	33	26	200	110	4.14
11.0246781	AW 36	25.1	502	260	22	19	36	29	260	140	6.22
11.0246782	AW 45	30.8	616	340	26	22	45	-	340	180	12.82
11.0260723	AW 50	40	800	350	32	26	50	43	350	190	16.55
11.0271783	AW 56	64	1,277	400	-	32	56	-	400	200	27.01
11.0254786	AW 72	85	1,700	460	-	-	70	-	460	250	45.3

# Blueprint

