Lifting Solutions Group
Axel Johnson International

Master Link Pewag AW

Product information



AW Master links are designed for the assembly of chain slings. For pewag connex and welded system.
Master link for 1-leg chain AI.
Master link for 2-leg chain AII.
Master link for 3- and 4-leg chain AIII/IV - only with transition link BW as on VW.
Can also be used as end link A I

... *Read more*

Material: High duty
Marking: According to standard, CE-mark, Pewag or PW, winner or 10, H16, batch code and type.
Temperature range: -40ºC up to +380°C.
Finish: Orange powder coated.
Standard: EN 1677-4

Safety factor: 4:1
Grade: 10


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Master Link Pewag AW

Blueprint



Technical data

Part code	Code	WLL ton	LC kN	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	d mm	s mm	t mm	w mm mm	Weight kg
402100230290	AW 13	2.3	46	110	6+7	6	13	10	110	60	0.34
402100350290	AW 16	3.5	70	110	8	7	16	14	110	60	0.53
402100500290	AW 18	5	100	135	10	8	19	14	135	75	0.92
402100760290	AW 22	7.6	152	160	13	10	23	17	160	90	1.6
402101000290	AW 26	10	200	180	16	13	27	20	180	100	2.46
402101400290	AW 32	14	280	200	19	16	33	26	200	110	4.14
402102510290	AW 36	25.1	502	260	22	19	36	29	260	140	6.22
402103080290	AW 45	30.8	616	340	26	22	45	-	340	180	12.82
402104000290	AW 50	40	800	350	32	26	50	43	350	190	16.55
402106400290	AW 56	64	1,277	400	-	32	56	-	400	200	27.01
402108500290	AW 72	85	1,700	460	-	-	70	-	460	250	45.3

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved