

Master Link Pewag MW Enlarged

Product information



MW Enlarged master links are designed for the assembly of chain slings. Can also be attached to wire rope slings. For pewag connex and welded system.

Master link SAW: Without flattened part for transition link and special colour [... Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Master Link Pewag MW Enlarged

Blueprint



Technical data

| Part code | Code | WLL ton | EWL | For chain, 1-leg mm | For chain, 2-leg mm | Use for hook DIN 15401 Nr | Double hook DIN 15402 no. | dmm | mm | smm | mm | t mm | w mm | mm | Weight kg |
|------------|-------|------------|-----|------------------------|------------------------|---------------------------|---------------------------|-----|----|-----|-----|-------|------|----|--------------|
| 11.0261990 | MW 10 | 1.4 | 90 | 5 | 5 | 2,5 | 4 | 11 | 10 | 90 | 65 | 0.22 | | | |
| 11.0261993 | MW 13 | 2.3 | 120 | 6+7 | 6 | 4 | 5 | 14 | 10 | 120 | 70 | 0.44 | | | |
| 11.0261996 | MW 16 | 3.2 | 140 | 8 | 7 | 5 | 6 | 16 | 13 | 140 | 80 | 0.71 | | | |
| 11.0262001 | MW 18 | 4.2 | 160 | 10 | 8 | 6 | 8 | 18 | 14 | 160 | 95 | 1.09 | | | |
| 11.0298533 | MW 22 | 6.7 | 170 | 13 | 10 | 10 | 12 | 23 | 17 | 170 | 105 | 1.74 | | | |
| 11.0262008 | MW 26 | 10.1 | 190 | 16 | 13 | 10 | 12 | 27 | 20 | 190 | 110 | 2.65 | | | |
| 11.0262011 | MW 32 | 16 | 230 | 19 | 16 | 12 | 16 | 33 | 26 | 230 | 130 | 4.78 | | | |
| 11.0262014 | MW 36 | 21.2 | 275 | 22 | 19 | 20 | 25 | 38 | 29 | 275 | 150 | 7.48 | | | |
| 11.0270801 | MW 56 | 40 | 350 | 32 | 26 | 50 | 63 | 56 | 46 | 350 | 250 | 21.98 | | | |