



Connex Connecting Link Pewag CLW

Product information

CLW Connex connecting for pewag connex system. For applications where the pin must not be removed or must be secured by positive locking.

Only for straight pull.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | EWL | b mm | c mm | d mm | e mm | g mm | s mm | t mm | Weight kg |
|------------|--------|---------|-----|------|------|------|------|------|------|------|-----------|
| 11.0657547 | CLW 7 | 1.9 | 51 | 47 | 10 | 9 | 51 | 17 | 13 | 14 | 0.12 |
| 11.0693058 | CLW 10 | 4 | 72 | 64 | 15 | 13 | 72 | 24 | 18 | 22 | 0.42 |
| 11.0640698 | CLW 13 | 6.7 | 88 | 79 | 20 | 17 | 88 | 28 | 22 | 26 | 0.84 |
| 11.0674337 | CLW 16 | 10 | 103 | 106 | 21 | 21 | 103 | 33 | 29 | 31 | 1.4 |

Blueprint

