MENNENS | Lifting Solutions Group
Axel Johnson International

Connex Connecting Link Pewag CLW

Product information



CLW Connex connecting for pewag connex system. For applications where the pin must not be removed or must be secured by positive locking.
Only for straight pull.

... *Read more*

Material: High duty grade 10.
Marking: According to standard, CE-mark, Pewag or PW, winner or 10, H16, batch code and type.
Temperature range: -40ºC up to +380°C.
Finish: Orange powder coated.
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Connex Connecting Link Pewag CLW

Blueprint



Technical data

Part code	Code	WLL ton	EWL mm	b mm	c mm	d mm	e mm	g mm	s mm	t mm	Weight kg
402200190130	CLW 7	1.9	51	47	10	9	51	17	13	14	0.12
402200400130	CLW 10	4	72	64	15	13	72	24	18	22	0.42
402200670130	CLW 13	6.7	88	79	20	17	88	28	22	26	0.84
402201000130	CLW 16	10	103	106	21	21	103	33	29	31	1.4

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved