



Safety Hook Pewag LHW

Product information

LHW Safety hooks are designed for the assembly of pewag connex system.

This hook has a large eye, which is suitable for ropes and webbing slings.

Automatically closes and locks under load and requires the load to be grounded before load can be released

Features:

- Self-closing and locking load hook
- Larger jaw opening than the HSW
- Locking set is available as a spare part

Marking: According to standard, CE-marked

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-3

Note: Not for welded system!

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | EWL | a mm | b mm | d1 mm | d2 mm | e mm | g mm | h mm | s max. mm | Weight kg |
|------------|-----------|---------|-----|------|------|-------|-------|------|------|------|-----------|-----------|
| 11.1649496 | LHW 5/6 | 1.4 | 110 | 17 | 71 | 21 | 11 | 110 | 28 | 20 | 1 | 0.53 |
| 11.1649497 | LHW 7/8 | 2.5 | 136 | 20 | 88 | 25 | 12 | 136 | 34 | 26 | 1 | 0.92 |
| 11.1649498 | LHW 10 | 4 | 169 | 29 | 107 | 35 | 15 | 169 | 45 | 30 | 1 | 1.57 |
| 11.1649499 | LHW 13 | 6.7 | 205 | 41 | 138 | 40 | 20 | 205 | 52 | 40 | 1.5 | 3.19 |
| 11.1649500 | LHW 16 | 10 | 251 | 50 | 168 | 50 | 27 | 251 | 60 | 50 | 2 | 6.24 |
| 11.1667163 | LHW 19/20 | 16 | 290 | 52 | 194 | 60 | 30 | 290 | 70 | 62 | 2 | 9.75 |
| 11.1667165 | LHW 22 | 19 | 322 | 61 | 211 | 70 | 32 | 322 | 81 | 65 | 2 | 12.45 |
| 11.1606300 | LHW 26 | 26.5 | - | 61 | 253 | 82 | 42 | 383 | 100 | 79 | 2 | 20 |

Blueprint

