MENNENS | Lifting Solutions Group
Axel Johnson International

Vertical lifting clamps Pewag BKW

Product information



For lifting and moving of steel beams, profiles and structures where the load must stay in position. The special shape of the lifting shackle places the centre of the gravity of the beam beneath the lifting shackle.

This maintains the equilibrium of the beam once it has been lifted and keeps the flanges vertical so that the beam can easily be stacked or positioned. Recommended for moving and stacking of steelbeams.

Lifting capacity and jaw-opening are clearly engraved in the body.

Minimum WLL is 10 % of the maximium WLL.

... *Read more*


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Vertical lifting clamps Pewag BKW

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	H mm	R mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Z mm	Weight kg
502100100150470	BKW 1 t	1	0-15	154	0-15	45	35	225	136	43	47	15	200	3
502100150200470	BKW 1.5 t	1.5	0-20	210	0-20	67	60	374	170	56	56	16	312	7
502100300250470	BKW 3 t	3	0-25	252	0-25	66	70	410	208	58	77	20	380	15

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved