Lifting Solutions Group
Axel Johnson International

Round Sling - Blackline

Product information



Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.
Design: Load carrying yarn covered with “seamless” black protection sleeve.
Stretch with working load: 2-3%.
Length tolerance: Nominal length (EWL) ±2%.

... *Read more*

Material: Polyester. Resistant to most acids but not to strong alkalizes.
Marking: According to standard, CE-mark, Manufacture ID, WLL, length, date.
Temperature range: Approx. -40° up to +100°C.
Standard: EN 1492-2

Safety factor: 7:1


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Round Sling - Blackline

Blueprint



Technical data

Part code	Code	WLL ton	EWL m	WLL Straight Lift ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	WLL 0-45° t	Colour
340100110100160	PRS-011.B	1.1	1	1.1	0.9	2.2	1.5	1.1	1.5	Black
340100210100160	PRS-021.B	2.1	1	2.1	1.7	4.2	2.9	2.1	2.9	Black
340100310100160	PRS-031.B	3.1	1	3.1	2.5	6.2	4.3	3.1	4.3	Black

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved