

## Lanyard with shock absorber, 3M Protecta Flex version

### Product information



3M, Protecta lanyard with shock absorber and elastic webbing, max. user weight 130 kg.

#### Connectors:

Harness side: Oval steel carabiner - opening 18mm

Anchorpoint side: Self locking galv. steel scaffold hook(s) - opening 50mm

**Life expectancy:** max. 10 years from manufacturing date.

#### Features:

- Elasticated webbing\* reduces lanyard length when not under tension which reduce the risk of trip and snagging hazards.
- 130 kg. Max rating allows a greater range of users.
- Small and compact shock absorber pack.
- Labels fully covered for long term identification.
- Lightweight. Helps reduce the carry weight of your equipment.
- Available in single-leg and twin-leg version

[... Read more](#)

**Material:** Elasticated webbing, Hooks and Carabiners Steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -35°C to +57°C

**Standard:** EN 355

## Lanyard with shock absorber, 3M Protecta Flex version

### Technical data

Part code	Length m	Number of legs	Max user weight kg	Weight kg
19.041260349	1.5	1	140	1
19.041260347	2	1	140	1.1
19.041260348	1.5	2	140	1.2
19.041260346	2	2	140	1.4