

## Fast Connector Socket FCS - with bolt



### Product information

Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.

The connector has to be moulded/casted on the steel wire rope with wirelock resin.

**Features:** Designed for use with mobile cranes.

**Material:** Quenched and tempered cast steel.

**Finish:** Blue painted or hot dip galvanized.

**Warning:** Compare the spelter's and the wire rope's minimum breaking load.

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm	TL mm	Weight kg
01-7015013B	FCS 701 B	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	80	150	1.6
01-7015016B	FCS 702 B	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	96	182	2.6
01-7015019B	FCS 703 B	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	107	218	4.5
01-7015023B	FCS 704 B	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	123	253	6.5
01-7015026B	FCS 705 B	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	141	298	11
01-7015029B	FCS 706 B	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	160	357	16

## Blueprint

