

Fast Connector Socket FCS

Product information



Forged clevis fittings with Pin and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only. The connector has to be moulded / casted on the steel wire rope with wirelock resin.

... [Read more](#)

Features: Designed for use with mobile cranes.


Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Fast Connector Socket FCS

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm mm	Ø P mm mm	T mm	W mm mm	D mm	Ø D mm mm	Ø J mm mm	K mm	TB mm mm	TL mm mm	Weight kg
01-7015013P	FCS 701 P	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	67	150	1.6
01-7015016P	FCS 702 P	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	85	182	2.6
01-7015019P	FCS 703 P	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	95	218	4.5
01-7015023P	FCS 704 P	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	110	253	6.5
01-7015026P	FCS 705 P	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	128	298	11
01-7015029P	FCS 706 P	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	142	357	16