MENNENS | Lifting Solutions Group
Axel Johnson International

Fast Connector Socket FCS

Product information



Forged clevis fittings with Pin and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.

The connector has to be moulded / casted on the steel wire rope with wirelock resin.

... *Read more*

Features: Designed for use with mobile cranes.
Material: Quenched and tempered cast steel.
Finish: Blue painted (P) or hot dip galvanized (G).
Warning: Compare the spelter's and the wire rope's minimum breaking load.

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Fast Connector Socket FCS

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm mm	TL mm mm	Weight kg
122101300165	FCS 701 P	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	67	150	1.6
122101600165	FCS 702 P	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	85	182	2.6
122101900165	FCS 703 P	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	95	218	4.5
122102200165	FCS 704 P	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	110	253	6.5
122102600165	FCS 705 P	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	128	298	11
122102900165	FCS 706 P	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	142	357	16

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved