



Short Bow Socket SBS

Product information

The "ultimate" socket for dynamic loads. Towing lines, anchor lines and chain-rope connections used by major offshore contractors. Quenched and tempered cast steel with extremely high mechanical values for unmatched weight to MBL ratio. All spelter sockets have a 100% efficiency on wire rope MBL.

The standard finish of our sockets is blue but hot dipped galvanized is also available.

Standard: EN 10204-2.1 declaration of conformity / EN 10204-3.1 material certificate.

Material: Quenched and tempered cast steel.

Marking: According to standard

Standard: EN 10204

| Part code | Rope Ø range mm | MBL ton | Finish | Model | Rope Ø inch | A mm | B mm | C mm | øH | K mm | TA mm | TL mm | Weight kg |
|----------------|-----------------|---------|---------|---------|-------------|------|------|------|-----|------|-------|-------|-----------|
| 10.42445120010 | 31-36 | 140 | Painted | SBS 512 | 11/4 - 13/8 | 141 | 83 | 38 | 39 | 75 | 132 | 262 | 7 |
| 10.42445170010 | 37-42 | 160 | Painted | SBS 517 | 11/2 - 15/8 | 162 | 103 | 40 | 44 | 92 | 152 | 305 | 10 |
| 10.424.5190010 | 43-48 | 200 | Painted | SBS 519 | 13/4 - 17/8 | 188 | 120 | 48 | 51 | 112 | 178 | 356 | 16 |
| 10.42445220010 | 49-54 | 250 | Painted | SBS 522 | 2 - 21/8 | 204 | 132 | 54 | 59 | 120 | 200 | 390 | 21 |
| 10.42445240010 | 55-60 | 320 | Painted | SBS 524 | 21/4 - 23/8 | 230 | 148 | 62 | 64 | 135 | 220 | 440 | 28 |
| 10.42445260010 | 61-68 | 400 | Painted | SBS 526 | 21/2 - 25/8 | 265 | 165 | 68 | 73 | 150 | 250 | 198 | 44 |
| 10.42445270010 | 69-75 | 500 | Painted | SBS 527 | 23/4 - 27/8 | 287 | 178 | 75 | 79 | 164 | 274 | 540 | 53 |
| 10.42445280010 | 76-80 | 600 | Painted | SBS 528 | 3 - 35/8 | 314 | 195 | 76 | 89 | 175 | 295 | 585 | 70 |
| 10.42445290010 | 81-86 | 700 | Painted | SBS 529 | 31/4 - 33/8 | 327 | 216 | 82 | 92 | 194 | 320 | 625 | 81 |
| 10.42445300010 | 87-93 | 800 | Painted | SBS 530 | 31/2 - 35/8 | 358 | 220 | 92 | 99 | 202 | 350 | 670 | 112 |
| 10.42445310010 | 94-102 | 900 | Painted | SBS 531 | 33/4 - 4 | 365 | 235 | 100 | 108 | 215 | 375 | 700 | 130 |
| 10.42445330010 | 108-115 | 1,000 | Painted | SBS 533 | 41/4 - 41/2 | 420 | 270 | 110 | 120 | 240 | 410 | 800 | 182 |

Blueprint

