

Standard Reeve Crane Blocks 2 Sheaves

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

... [Read more](#)

Standard Reeve Crane Blocks 2 Sheaves

Blueprint



Technical data

WLL ton	Model	Rope Ø mm	Hooksize	Weight kg
16	SRB 285 .16 .2 .16 .E	16	6	95
16	SRB 260 .14 .2 .16 .E	14	6	130
16	SRB 260 .16 .2 .16 .E	16	6	130
20	SRB 285 .16 .2 .20 .E .A	16	8	130
20	SRB 285 .16 .2 .20 .E .B	16	8	150
20	SRB 320 .16 .2 .20 .E	16	8	160
25	SRB 320 .16 .2 .25 .E	16	8	205
29	SRB 355 .19 .2 .29 .E	19	8	250
29	SRB 400 .22 .2 .29 .E	22	8	320
40	SRB 450 .24 .2 .40 .E	24	12	550
50	SRB 450 .26 .2 .50 .E	26	16	550
63	SRB 528 .26 .2 .63 .E	26	16	980
80	SRB 528 .28 .2 .80 .E	28	20	1,000
100	SRB 670 .28 .2 .100 .E	28	20	2,240
100	SRB 670 .32 .2 .100 .E	32	20	2,240