

Fast Reeve Crane Blocks 2 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 2 sheave

Blueprint



Fast Reeve Crane Blocks 2 sheave

Technical data

WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hooksize	øD1 mm	øD2 mm	B mm	Omm mm	TA mm mm	TBmm mm	TLmm mm	L mm	T mm	øZ mm	Weight kg
16	FRB 225 .14 .2 .16 .E	14	260 / 255	6	260	225	608	59	345	180	883	1,103	28	32	105
16	FRB 260 .14 .2 .16 .E	14	300 / 260	6	300	260	693	59	400	165	978	1,168	28	32	125
16	FRB 260 .16 .2 .16 .E	16	300 / 260	6	300	260	693	59	400	165	978	1,168	28	32	125
20	FRB 260 .14 .2 .20 .E	14	300 / 260	8	300	260	748	69	400	165	1,033	1,103	28	32	130
20	FRB 260 .16 .2 .20 .E	16	300 / 260	8	300	260	748	69	420	165	1,033	1,213	28	32	130
20	FRB 285 .16 .2 .20 .E	16	365 / 285	8	365	285	778	69	420	165	1,078	1,236	28	32	160
20	FRB 320 .16 .2 .20 .E	16	365 / 320	8	365	320	768	69	450	180	1,101	1,231	28	32	160
25	FRB 320 .16 .2 .25 .E	16	365 / 320	8	365	320	763	69	450	130	1,096	1,333	28	32	205
29	FRB 355 .19 .2 .29 .E	19	410 / 355	8	410	355	848	69	500	225	1,193	1,393	35	37	265
29	FRB 400 .19 .2 .29 .E	19	460 / 400	8	460	400	873	69	570	240	1,253	1,398	35	37	365
29	FRB 400 .22 .2 .29 .E	22	460 / 400	8	460	400	873	69	570	240	1,253	1,572	40	43	365
32	FRB 450 .22 .2 .32 .E	22	515 / 450	10	515	450	1,003	76	600	250	1,416	1,655	40	43	485
40	FRB 450 .22 .2 .40 .E	22	515 / 450	12	515	450	1,074	84	600	333	1,487	1,665	40	43	590
40	FRB 450 .24 .2 .40 .E	24	515 / 450	12	515	450	1,074	84	600	333	1,487	1,689	45	52	590
40	FRB 450 .26 .2 .40 .E	26	515 / 450	12	515	450	1,074	84	600	333	1,497	1,689	45	52	590
50	FRB 450 .24 .2 .50 .E	22	515 / 450	16	515	450	1,074	97	600	363	1,497	1,675	45	52	680
50	FRB 450 .26 .2 .50 .E	26	515 / 450	16	515	450	1,074	97	600	363	1,497	1,848	45	52	680
63	FRB 528 .24 .2 .63 .E	24	595 / 528	16	595	528	1,202	97	710	383	1,656	1,848	45	52	1,000
63	FRB 528 .26 .2 .63 .E	26	595 / 528	16	595	528	1,202	97	710	383	1,656	1,946	45	52	1,000
63	FRB 528 .28 .2 .63 .E	28	595 / 528	16	595	528	1,203	97	710	383	1,681	1,971	50	59	1,000
80	FRB 528 .26 .2 .80 .E	26	595 / 528	20	595	528	1,272	110	710	412	1,736	1,883	45	52	1,065
80	FRB 528 .28 .2 .80 .E	28	595 / 528	20	595	528	1,273	110	710	412	1,751	2,117	50	59	1,065
100	FRB 670 .28 .2 .100 .E	28	760 / 670	20	760	670	1,332	110	870	482	1,897	2,122	50	59	2,240
100	FRB 670 .32 .2 .100 .E	32	760 / 670	20	760	670	1,332	110	870	482	1,897	3,122	60	66	2,240