



Fast Reeve Crane Blocks 6 sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Safety factor: 4:1

WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hooksize	B mm	L	O mm	T mm	TA mm	TB mm	TL mm	Ø D1 mm	Ø D2 mm	Ø Z mm	Weight kg
63	FRB 360 .19 .6 .63 .E .A	19	420 / 360	16	973	-	97	30	510	522	1,243	420	360	37	680
63	FRB 360 .19 .6 .63 .E .B	19	420 / 360	16	973	-	97	30	510	522	1,243	420	360	37	725
63	FRB 400 .19 .6 .63 .E	19	460 / 400	16	1,063	-	97	30	570	507	1,363	460	400	37	775
80	FRB 400 .19 .6 .80 .E	19	460 / 400	20	1,147	1,597	110	30	570	507	1,447	460	400	43	820
80	FRB 400 .22 .6 .80 .E	22	460 / 400	20	1,147	1,597	110	40	570	507	1,447	460	400	43	820
80	FRB 450 .22 .6 .80 .E	22	515 / 450	20	1,187	1,730	110	40	600	502	1,580	515	450	43	910
80	FRB 450 .24 .6 .80 .E	24	515 / 450	20	1,187	1,730	110	45	600	502	1,580	515	450	52	910
100	FRB 450 .24 .6 .100 .E	24	515 / 450	25	1,263	1,768	132	45	600	582	1,598	515	450	52	1,135
100	FRB 450 .26 .6 .100 .E	26	515 / 450	25	1,263	1,768	132	45	600	582	1,598	515	450	52	1,135
150	FRB 528 .24 .6 .150 .E	24	596 / 528	40	1,553	2,232	167	45	710	642	2,020	596	528	52	1,800
150	FRB 528 .26 .6 .150 .E	26	596 / 528	40	1,553	2,232	167	45	710	642	2,020	596	528	52	1,800
150	FRB 528 .28 .6 .150 .E	28	596 / 528	40	1,553	2,242	167	50	710	642	2,030	596	528	59	1,800
160	FRB 528 .26 .6 .160 .E	26	596 / 528	40	1,581	2,178	167	45	710	682	1,966	596	528	52	2,270
160	FRB 528 .28 .6 .160 .E	28	596 / 528	40	1,581	2,188	167	50	710	682	1,976	596	528	59	2,270
200	FRB 575 .28 .6 .200 .E	28	650 / 575	50	1,661	2,317	188	50	770	602	2,081	650	575	59	2,270
235	FRB 670 .28 .6 .235 .E	28	760 / 670	50	1,716	2,442	188	50	870	952	2,206	760	670	59	4,160
235	FRB 670 .32 .6 .235 .E	32	760 / 670	50	1,716	2,442	188	60	870	952	2,206	760	670	66	4,160

Blueprint

