

## Samson wire rope blocks 2 sheave

---

### Product information



#### General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

... [Read more](#)

---


**Temperature range:** -40°C / +80°C

**Note:** WLL= Working Load Limit on head fitting.

**Safety factor:** 4:1

## Samson wire rope blocks 2 sheave

### Blueprint



### Technical data

Part code	WLL ton	Rope Ø mm	No of Sheaves	Weight kg
16.13111000120	1	8	2	4
16.13111250220	1.5	10	2	6
16.13111500320	3	12	2	11
16.13112000420	4	14	2	18
16.13112500620	6	18	2	32
16.13113000820	8	20	2	43
16.1311.501020	10	22	2	74
16.13113501220	12	22	2	81
16.13114001220	12	24	2	102
16.13113501620	16	22	2	98
16.13114001620	16	24	2	126
16.13113502020	20	22	2	116
16.13114002020	20	24	2	146
16.13114002520	25	24	2	169
16.13114502520	25	28	2	190
16.13114003020	30	24	2	184
16.13114503020	30	28	2	204
16.13114504020	40	28	2	225