

Samson wire rope blocks 3 sheave

Product information



General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

... [Read more](#)


Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting

Safety factor: 4:1

Samson wire rope blocks 3 sheave

Blueprint



Technical data

Part code	WLL ton	Rope Ø mm	No of Sheaves	Weight kg
424100200330	2	10	3	9
424100400330	4	12	3	17
424100600330	6	14	3	28
424100800330	8	18	3	46
424101000330	10	20	3	69
424101200330	12	22	3	99
424101600330	16	24	3	120
424101600335	16	24	3	157
424102000335	20	24	3	143
424102000330	20	24	3	184
424102500330	25	24	3	170
424102500335	25	24	3	198
424102500336	25	28	3	220
424103000330	30	28	3	215
424103000335	30	28	3	255
424104000330	40	28	3	250
424104000335	40	28	3	295
424105000330	50	28	3	335