

Safety Harness ExoFit™ XE50 1112702 / 03 / 04

Informations du produit



The 3M™ DBI-SALA® ExoFit™ XE50 is designed with high-quality components specially developed for enhanced safety and fit while working at heights. Built with durable 26kN polyester webbing and alloy steel hardware, 3M™ DBI-SALA® ExoFit™ XE50 was created to endure the daily conditions of your job site.

The back D-ring plate design with pSRL tunnel allows quick and easy connection of a personal SRL. Revolving torso-adjustment buckles and buckles will help get your team get a quick, safe, and comfortable harness fit. This harness is compatible with optional accessory for back/shoulder padding, leg padding and with variety of 3M fall protection for tools accessories.

All models are equipped with low-profile suspension trauma relief straps.

Attachment point:

- Rear: Large D-ring – Steel - zinc plated
- Front: Standard D-ring– Steel - zinc plated

Buckles:

- Legs: Pass-through– Steel - zinc plated/black paint
- Chest: Pass-through – Steel - zinc plated/black paint

Size adjustment:

- Legs and Torso
- Torso: Revolving adjuster – Steel/aluminium - ratchet buckle

Additional features:

- Front & rear fall indicators
- 2x Auto-resetting/repositionable lanyard keepers
- RFID Equipped
- Dedicated personal self-retracting lifeline attachment point


... [En savoir plus](#)

Marquage: Selon la norme, Marqué CE, Marqué UKCA

Norme: EN 361

Safety Harness ExoFit™ XE50 1112702 / 03 / 04

Dessin technique



Données techniques

| Réf. | Taille | Charge maximale kg | Poids (kg) |
|---------|--------|-----------------------|---------------|
| 1112702 | 1 | 140 | 1,65 |
| 1112703 | 2 | 140 | 1,7 |
| 1112704 | 3 | 140 | 1,75 |