

Short Link Lifting Chain POWERTEX PSLA

Informations du produit



The Powertex Grade 10 PSLA Lifting Chain is a reliable lifting chain intended for use in demanding industrial applications. This high-quality calibrated lifting chain ensures safety, durability, and compliance, making it the smart choice for your lifting needs.

Product benefits

- **Safe and tested:** each chain link is proof load tested to 2.5 times the Working Load Limit (WLL) before delivery. Additionally, each production batch undergoes rigorous testing to meet the minimum breaking force and elongation requirements, ensuring maximum safety in every use.
- **Long-lasting durability:** PSLA features a durable electrophoretic wet paint (E-coat) finish in blue, providing superior resistance to wear and corrosion. This ensures the chain remains reliable and functional even in demanding environments.
- **Exceptional ductility:** The chain offers great ductility, with a minimum elongation of 20% before failure, providing flexibility and resilience during lifting operations.
- **Accurate:** Each chain length is calibrated in the factory before delivery, ensuring accurate and consistent performance in every application.
- **Consistent Quality:** PSLA is manufactured using automatic chain welding machines, guaranteeing consistent quality and reliability, giving you peace of mind during critical lifting tasks.
- **Compliance and Certification:** The chains fulfill the Machinery Directive 2006/42/EC, ensuring they meet stringent safety and quality standards. Each box includes a 14-language 2.2 Certificate and EC/UKCA Declaration of Conformity, providing comprehensive documentation for compliance. [... En savoir plus](#)

Marquage: Selon la norme, Marqué CE, Marqué UKCA


Norme: EN 818-2 (+ 25% WLL), AS 2321, ASTM A973/A973M

Coefficient de sécurité: 4:1

Grade: 10

Short Link Lifting Chain POWERTEX PSLA

Dessin technique



Données techniques

Réf.	Diamètre chaîne mm	CMU tonne(s)	Rupture min. kN	Pas	Modèle	dmm mm	pmm mm	W1 min. mm	W2 max mm mm	Poids kg/m
PSLA-6-10	6	1,4	56,5	18	PSLA-6-10	6	18	7,8	22,2	0,8
PSLA-7-10	7	1,9	77	21	PSLA-7-10	7	21	9,1	25,9	1,2
PSLA-8-10	8	2,5	101	24	PSLA-8-10	8	24	10,4	29,6	1,5
PSLA-10-10	10	4	157	30	PSLA-10-10	10	30	13,0	37,0	2,3
PSLA-13-10	13	6,7	265	39	PSLA-13-10	13	39	16,9	48,1	3,9
PSLA-16-10	16	10	402	48	PSLA-16-10	16	48	20,8	59,2	5,8
PSLA-19-10	19	14	567	57	PSLA-19-10	19	57	24,7	70,3	8,4
PSLA-20-10	20	16	628	60	PSLA-20-10	20	60	26,0	74,0	8,9
PSLA-22-10	22	19	760	66	PSLA-22-10	22	66	28,6	81,4	11,4