



Aluminum Chain Block Powertex PACB-S10LP

Informations du produit

Extremely small and lightweight aluminum chain block. It weighs only approximately 50% of a similar standard chain block. The block can be used for lifting as well as pulling. The hoists are factory equipped with overload protection device (OLP), which limits the maximum operating force that can be applied using the hand chain.

Features:

- Safe - Each block is dynamic proof load tested 1,5 x WLL before leaving the factor
- Compact, lightweight construction with aluminum covers
- Durable construction with powder coated finish and plated frame parts
- Chain block is chromium 6 free
- Sealed bearings on the chain wheel maximize efficiency and serviceability.
- Sprocket wheel surface treated against wear and corrosion
- Safe and well covered automatic load reaction break
- Equipped with double brake pawls
- Fine calibrated Electro Galvanized (European made) load chain for smooth operation
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- 14 language User Manual enclosed with each hoist
- Spare parts available

Marquage: Selon la norme

Norme: EN 13157, EN 818-7

Coefficient de sécurité: 4:1

Réf.	CMU tonne(s)	Hauteur de levage m	Nb de brins	Modèle	Chaîne de charge mm	Chaîne de manoeuvre mm	Effort sur chaîne de manoeuvre max. kg	Longueur chaîne de manoeuvre m	A B C D E F H Poids mmmmmmmmmmmin (kg) mm
16.10PACBS10025030OLP	0,25	3	1	PACB- S1OLP/250	3,0 x 9	2,5 x 12	15	2,5	75 77 44 32 35,5 21 225 2,6
16.10PACBS10025060OLP	0,25	6	1	PACB- S1OLP/250	3,0 x 9	2,5 x 12	15	2,5	75 77 44 32 35,5 21 225 3,8
-	0,25	10	1	PACB- S1OLP/250	3,0 x 9	2,5 x 12	15	2,5	75 77 44 32 35,5 21 225 5,4
16.10PACBS10050030OLP	0,5	3	1	PACB- S1OLP/500	4,0 x 12	3,5 x 16	19	2,5	92 89 51 34,5 42 23 265 4,6
16.10PACBS10050060OLP	0,5	6	1	PACB- S1OLP/500	4,0 x 12	3,5 x 16	19	2,5	92 89 51 34,5 42 23 265 6,1
16.10PACBS10100030OLP	1	3	1	PACB- S1OLP/1000	5,6 x 15,7	3,5 x 16	29	2,5	110 102 55 42,5 49,5 27 295 6,6
16.10PACBS10100060OLP	1	6	1	PACB- S1OLP/1000	5,6 x 15,7	3,5 x 16	29	2,5	110 102 55 42,5 49,5 27 295 10,14
16.10PACBS10200030OLP	2	3	1	PACB- S1OLP/2000	8,0 x 24	4,8 x 22	37	2,5	145 138 78,5 46,5 58,5 35 390 13,5
16.10PACBS10200060OLP	2	6	1	PACB- S1OLP/2000	8,0 x 24	4,8 x 22	37	2,5	145 138 78,5 46,5 58,5 35 390 20,4
16.10PACBS10300030OLP	3	3	2	PACB- S1OLP/3000	7,1 x 20,1	4,8 x 22	35	2,5	165 120 68 50 61,9 37 470 17
16.10PACBS10300060OLP	3	6	2	PACB- S1OLP/3000	7,1 x 20,1	4,8 x 22	35	2,5	165 120 68 50 61,9 37 470 26,3

Dimensions

