MENNENS | Lifting Solutions Group
Axel Johnson International

Aluminum Chain Block Powertex PACB-S1OLP

Informations du produit



Extremely small and lightweight aluminum chain block. It weighs only approximately 50% of a similar standard chain block. The block can be used for lifting as well as pulling. The hoists are factory equipped with overload protection device (OLP), which limits the maximum operating force that can be applied using the hand chain.

Features:

- Safe - Each block is dynamic proof load tested 1,5 x WLL before leaving the factor
- Compact, lightweight construction with aluminum covers
- Durable construction with powder coated finish and plated frame parts
- Chain block is chromium 6 free
- Sealed bearings on the chain wheel maximize efficiency and serviceability.
- Sprocket wheel surface treated against wear and corrosion
- Safe and well covered automatic load reaction break
- Equipped with double brake pawls
- Fine calibrated Electro Galvanized (European made) load chain for smooth operation
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals

... *En savoir plus*

Marquage: Selon la norme
Norme: EN 13157, EN 818-7

Coefficient de sécurité: 4:1


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© Novembre 2026 - Tous droits réservés

MENNENS | Lifting Solutions Group
Axel Johnson International

Aluminum Chain Block Powertex PACB-S1OLP

Dessin technique



Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© Novembre 2026 - Tous droits réservés

MENNENS | Lifting Solutions Group
Axel Johnson International

Aluminum Chain Block Powertex PACB-S1OLP

Données techniques

Réf.	CMU tonne(s)	Hauteur de levage m	Nb de brins	Modèle	Chaîne de charge mm	Chaîne de manoeuvre mm	Effort sur chaîne de manoeuvre max. kg	Longueur chaîne de manoeuvre m	A mm	B mm	C mm	D mm	E mm	F mm	H min mm	Poids (kg)
500100030300241	0,25	3	1	PACB-S1OLP/250/PHCA-S1	3,0 x 9	2,5 x 12	15	2,5	75	77	44	32	35,5	21	225	2,6
500100030600241	0,25	6	1	PACB-S1OLP/250/PHCA-S1	3,0 x 9	2,5 x 12	15	2,5	75	77	44	32	35,5	21	225	3,8
500100031000240	0,25	10	1	PACB-S1OLP/250/PHCA-S1	3,0 x 9	2,5 x 12	15	2,5	75	77	44	32	35,5	21	225	5,4
500100050300241	0,5	3	1	PACB-S1OLP/500/PHCA-S1	4,0 x 12	3,5 x 16	19	2,5	92	89	51	34,5	42	23	265	4,6
500100050600241	0,5	6	1	PACB-S1OLP/500/PHCA-S1	4,0 x 12	3,5 x 16	19	2,5	92	89	51	34,5	42	23	265	6,1
500100100300241	1	3	1	PACB-S1OLP/1000/PHCA-S1	5,6 x 15,7	3,5 x 16	29	2,5	110	102	55	42,5	49,5	27	295	6,6
500100100600241	1	6	1	PACB-S1OLP/1000/PHCA-S1	5,6 x 15,7	3,5 x 16	29	2,5	110	102	55	42,5	49,5	27	295	10,14
500100200300241	2	3	1	PACB-S1OLP/2000/PHCA-S1	8,0 x 24	4,8 x 22	37	2,5	145	138	78,5	46,5	58,5	35	390	13,5
500100200600241	2	6	1	PACB-S1OLP/2000/PHCA-S1	8,0 x 24	4,8 x 22	37	2,5	145	138	78,5	46,5	58,5	35	390	20,4
500100300300241	3	3	2	PACB-S1OLP/3000/PHCA-S1	7,1 x 20,1	4,8 x 22	35	2,5	165	120	68	50	61,9	37	470	17
500100300600241	3	6	2	PACB-S1OLP/3000/PHCA-S1	7,1 x 20,1	4,8 x 22	35	2,5	165	120	68	50	61,9	37	470	26,3

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© Novembre 2026 - Tous droits réservés