



Worm Gear Hand Winch WW2000-7500 Painted

Informations du produit

This hand winch is very safe due to the natural braking effect of the worm gear transmission in combination with the load pressure brake. In addition, the winch is easy to use, can be mounted in various ways and has a cable storage up to 120 meters.

- winch suitable for lifting and pulling
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- free-spooling device for pulling applications. To disengage the drum (FS)
- free-spooling device with additional friction brake for controlled cable unwinding (FSB)
- ATEX certified zone 2 and 22 (EX)
 - CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
 - CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

Marquage: Selon la norme, Marqué CE

Norme: EN 13157

Coefficient de sécurité: 4:1

