



Kiswire Steel Wire Rope 19x7 | semi-rotation resistant

Informations du produit



Semi-rotation resistant galvanized multistrand lifting cable from the renowned steel wire rope manufacturer Kiswire. High- and consistent quality guaranteed!

Applications: Suitable for, for example, cranes, electric hoists, winches and other applications where a semi-rotation resistant construction is enough.

Laying method: RHOL Right-Hand-Ordinary-Lay, sZ (standard), Lang's Lay (zZ) on request

ISO 4309 Cable Category No.: all diameters RCN.23-1

Marquage: Selon la norme

Norme: EN 12385-4

RCN: 23-1

Réf.	Dia. câble mm	Classe de résistance N/mm ²	Finition	Sens de câblage	Rupture min. kN	Graissage	Poids kg/100m
102100604270382	6	1 960	Acier galvanisé	sZ	23,1	A-2	15,1
102100704270382	7	1 960	Acier galvanisé	sZ	31,5	A-2	20,6
102100804270382	8	1 960	Acier galvanisé	sZ	41,1	A-2	26,9
102100904270382	9	1 960	Acier galvanisé	sZ	52,1	A-2	34,1
102101004270382	10	1 960	Acier galvanisé	sZ	64,3	A-2	42,1
102101104270382	11	1 960	Acier galvanisé	sZ	77,8	A-2	51
102101204270382	12	1 960	Acier galvanisé	sZ	92,6	A-2	60,8
102101304270382	13	1 960	Acier galvanisé	sZ	109	A-2	71,2
102101404270382	14	1 960	Acier galvanisé	sZ	126	A-2	81,9
102101604270382	16	1 960	Acier galvanisé	sZ	165	A-2	107
102101804270382	18	1 960	Acier galvanisé	sZ	217	A-2	137
102102004270382	20	1 960	Acier galvanisé	sZ	273	A-2	170
102102204270382	22	1 960	Acier galvanisé	sZ	311	A-2	195