

## Vacuum Lifting Beam CLAD-MAN®

### Informations du produit



moving limits

The CLAD-MAN® vacuum lifting beam is the all-rounder for XXL jobs at the construction site. The vacuum lifting beam makes the mounting easier and increases the safety and the efficiency substantial.

#### Suitable for lifting of:

- Panels up to 26 meters long
- Trapezoidal elements
- Roof and wall elements weighing up to 800 kg
- Rotatable by up to 90°
- Roof slope up to 45°

#### An all-round tool...

CLAD-MAN® is designed for outdoor as well as indoor use and can be used together with a crane, telescope loading machine, truck or similar. The lifting beam works without power connection due to the built-in batteries with integrated charger.

Thanks to the 2-circuit system, the digital vacuum sensor technology and optional belt safety system, CLAD-MAN® delivers maximum safety for personnel and materials under harsh on-site conditions. The unique belt system allows for very fast and safe placement of the belts.

The vacuum-actuated pump control (Ecomatic) makes sure that the batteries are taken good care of. A long workday on site poses a great challenge for personnel and equipment. You can rely on CLAD-MAN®'s consistent level of performance and intelligent energy management.

The modular design with the wide variety of option packs offers the right solution for every application. CLAD-MAN® is the ideal partner when it is necessary to install especially long wall or roof panels or heavy trapezoidal sheets on sloped roofs with a pitch of up to 45°.

#### Product variants

The CLAD-MAN vacuum lifter is available in different versions with:

- horizontal load capacities from 400 to 800 kg
- vertical load capacities from 400 to 800 kg
- 8 to 16 suction plates
- different lifting beam lengths, etc.

We will happily advise you on selecting a suitable device for your application.

CMU tonne(s)	Modèle	Portée mm	Nombre de pistons / dimensions mm	Taille maximale des matériel* mm	CMU verticale Tonnes	B SPL mm mm	L SPL mm mm	EH mm mm	Lmm mm	Poids (kg)
0,4	CLAD-MAN-D-400/8L/16000	16 000	8 - 140x650	26 000	-	140	650	1 280	16 000	570
0,6	CLAD-MAN-D-600/8L/4000	4 000	8- 140x650	14 000	0,4	140	650	1 280	4 000	370
0,8	CLAD-MAN-D-800/12L/3000	3 000	12 - 140x650	13 000	0,6	140	650	1 280	3 000	400
0,8	CLAD-MAN-W-800/16L/3000	3 000	16 - 140x650	12 000	0,8	140	650	1 280	3 000	475

## Dimensions

