



## 8x19W + âme acier

### Informations du produit

Général : Composition standard à 8 torons

### Données techniques

| Dia. (mm) | CRM 1770N/mm <sup>2</sup> (kN) | CRM 1960N/mm <sup>2</sup> (kN) | Poids (kg/100m) |
|-----------|--------------------------------|--------------------------------|-----------------|
| 8         | 40.3                           | 44.7                           | 26              |
| 9         | 51                             | 56.5                           | 33              |
| 10        | 63                             | 69.8                           | 40.7            |
| 11        | 76.2                           | 84.4                           | 49.2            |
| 12        | 90.7                           | 100                            | 58.6            |

|    |      |      |      |
|----|------|------|------|
| 13 | 106  | 118  | 68.8 |
| 14 | 124  | 137  | 79.8 |
| 16 | 161  | 179  | 104  |
| 18 | 204  | 226  | 132  |
| 20 | 252  | 279  | 163  |
| 22 | 305  | 338  | 197  |
| 24 | 363  | 402  | 234  |
| 26 | 426  | 472  | 275  |
| 28 | 494  | 547  | 319  |
| 32 | 645  | 715  | 417  |
| 36 | 817  | 904  | 527  |
| 40 | 1010 | 1120 | 651  |
| 44 | 1220 | 1350 | 788  |
| 48 | 1450 | 1610 | 938  |
| 52 | 1700 | 1890 | 1100 |
| 56 | 1980 | 2190 | 1280 |
| 60 | 2270 | 2510 | 1470 |