

Accessoires pour vérin de 5-10 tonnes

Informations du produit



Réf.	Description
100.002.966	• To provide better grip• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
100.002.968	• For spreading• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
100.002.969	• Suitable for HGC 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar• Standard supplied with 2x bolt M8x16
100.002.978	• To mount on bottom side of cylinder• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 360 bar
100.002.980	• To connect 2 extension tubes• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female (2x)• Max. working pressure: 360 bar
100.002.982	• To connect accessories to cylinders• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
100.002.984	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 125 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
100.002.985	• Suitable for HGC 10 & HCJ 10 cylinders• Length: 250 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
100.002.987	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 500 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
100.002.989	• Suitable for HGC 10 and HCJ 10 cylinders• Length: 750 mm• Thread size: 1¼" NPT male (2x)• Max. working pressure: 360 bar
100.002.991	• Suitable for HGC 10 and HCJ 10 cylinders• Thread size: 1¼" NPT female• Max. working pressure: 144 bar
100.002.992	• Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS female• Max. working pressure: 144 bar
100.002.993	• Suitable for HCJ 10 cylinders• Thread size: M60x2 female• Max. working pressure: 144 bar
100.003.004	• Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20
100.003.004	• Suitable for HGC 5 and HGC 10• Max. working pressure: 720 bar• Standard supplied with 2x bolt M8x20 and 2x bolt M6x20
100.181.091	• Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT female
100.181.519	• Suitable for HCJ 10 cylinders• Thread size: 1¼" NPT male
100.181.522	• Suitable for HCJ 10 cylinders• Thread size: M60x2• Max. working pressure: 720 bar
100.182.189	• Suitable for HGC 5 cylinders• Thread size: 1½"-16 UN• Max. working pressure: 720 bar
100.182.190	• Suitable for HGC 10 cylinders• Thread size: 2¼"-14 UNS• Max. working pressure: 720 bar